LIGHTING SYSTEM

FIVELIE	E SYMBOL	DESCRIPTION		LAMP CHARACTERISTICS					
FIXTURE REF.			IP	NO. OF LAMP	POWER	LUM.	CLRT	CRI	MOUNT
L1	•	LED STREET LIGHT, FULLY DIE-CAST ALUMINUM BODY WITH GLASS COVER , ON STEEL ARM .	65	1	96W	10000	3500K	≥ 70	WALL
L2		LED STREET LIGHT, FULLY DIE-CAST ALUMINUM BODY WITH GLASS COVER , ON 7M STEEL POLE (SINGLE ARM).	65	1	96W	10000	3500K	> 70	POLE

GENERAL NOTES

- 1. THIS DRAWING WILL BE READ IN CONJUNCTION WITH ALL RELEVANT DRAWING BILL OF QUANTITIES AND LOCAL STANDARDS, AND ALL THE WORKS WILL BE EXECUTED ACCORDINGLY.
- 2. ALL OUTDOOR INSTALLATIONS SHALL BE WEATHER PROOF TYPE OR ENCLOSED IN (W.P.)ENCLOSURES WHETHER INDICATED OR NOT ON DRAWINGS OR IN BILL OF QUANTITES.
- 3. ALL DRAW BOXES SHALL BE GOOD LABLED.
- 4. ALL EXPOSED CONDUITS WILL BE STEEL GALVANIZED CONDUITS.
- 5. THE CONTRACTOR SHALL ATTEND ON AND PROVIDE ALL FACILITIES TO THE LOCAL STANDARDS AND SHALL PROVIDE